

### Features

- Exquisite design with precision measurement and craftsmanship
- Blue zinc mounting profiles, free of static
- Toughened glass front door with obliquely vented door border and three section vented rear door
- Adjustable feet and heavy duty castors are available simultaneously
- Cable entry on the top cover and bottom panel with adjustable sizes
- Optional installation of plinth to enable cabinets fixations, under base entry cable entry/ ventilation
- Removal side panel for easy maintenance



### Oranment Strip Color

### Body Color



Light Red



Light Blue



Black RAL 9004



Gray RAL 7035



Cooling Fan



Cable manager with cap



Welded frame with strong structure



Advanced moon Shaped lock



## Load Capacity

- Static Loading : 800Kg (with adjustable feet)
- Load capacity can be customize

## Standards

ANS/EIA RS-310-D,IEC297-2,DIN41491,PART1,  
 DIN41491,PART7,ETSI Standard  
 CE Compliant  
 RoHS Compliant

## Specification

Standard	ANS/EIA RS-310-D,IEC297-2,DIN41491,PART1,DIN41491,PART7,ETSI Standard
Material	SPCC quality cold rolled steel Thickness:mounting Profile:2.0mm,Others:1.2mm
Loading Capacity	Tempered glass Thickness:5mm
Degree of protection	Static loading: 800kg (on the adjustable feet)
Surface finish	IP20
Product specification	Degreasing,Pickling,Phosphating,Powder Coated
Width	18U-47U
Depth	600mm,800mm
Color	600mm,800mm,900mm,1000mm,1200mm
	Ral9004; Ral9005; Ral7035

## Doors

- Steel casement door
- Smoky-gray glass door
- Smoky-gray glass door with frame punched
- Perforated steel door
- Double Perforated steel door
- Double swing steel door

## ORDERING INFORMATION

PART NUMBER	WIDTH	DEPTH	HEIGHT
APFS-6647	600	600	2200
APFS-6847	600	800	2200
APFS-6147	600	1000	2200
APFS-8847	800	800	2200
APFS-8147	800	1000	2200

