



Features:

- Solid and reliable terminations for copper cabling featuring a minimum of 3 mm 50 micro-inch gold-plated jack contacts
- Compatible with both 110 and Krone punch-down tools
- Supports 22 to 26 AWG stranded and solid wire
- For use with unshielded twisted pair (UTP) Cat6 network cable
- Ideal for Ethernet, Fast Ethernet and Gigabit Ethernet network applications
- Connects 24 RJ-45 ports to a network
- Occupies 1U rack height
- Meets 19" rackmount standards

Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (1000Base-T Gigabit Ethernet)

Environmental

- Dimensions: 482 mm (W) x 43 mm (H) x 48 mm (D) (19 x 1.7 x 1.9 in.)
- Horizontal distance between left and right mounting holes: 465 mm (18.3 in.)
- Vertical distance between top and bottom mounting holes: 31.8 mm (1.25 in.)
- Weight: 0.76 kg (1.67 lbs.)
- Operating temperature: -40 – 80°C (-40 – 176°F)

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
APP-C6-2724	Category 6 Unshielded 24 port Loaded patch panel
APP-C6-2748	Category 6 Unshielded 48 port Loaded patch panel

