


Features

- Exquisite design with precision measurement and craftsmanship
- Blue zinc mounting profiles, free of static
- Toughened glass front door with obliquely vented door border and three section vented rear door
- Adjustable feet and heavy duty castors are available simultaneously
- Cable entry on the top cover and bottom panel with adjustable sizes
- Optional installation of plinth to enable cabinet fixations, under base entry cable entry/ ventilation
- Removal side panel for easy maintenance



Oranment Strip Color

Body Color



Light Red



Light Blue



Black RAL 9004



Gray RAL 7035



Cooling Fan



Cable manager with cap



Welded frame with strong structure



Advanced moon Shaped lock



Load Capacity

- Static Loading : 800Kg (with adjustable feet)
- Load capacity can be customize

Standards

ANS/EIA RS-310-D,IEC297-2,DIN41491,PART1,
 DIN41491,PART7,ETSI Standard
 CE Compliant
 RoHS Compliant

Specification

Standard	ANS/EIA RS-310-D,IEC297-2,DIN41491,PART1,DIN41491,PART7,ETSI Standard
Material	SPCC quality cold rolled steel Thickness:mounting Profile:2.0mm,Others:1.2mm
Loading Capacity	Tempered glass Thickness:5mm
Degree of protection	Static loading: 800kg (on the adjustable feet)
Surface finish	IP20
Product specification	Degreasing,Pickling,Phosphating,Powder Coated
Width	18U-47U
Depth	600mm,800mm
Color	600mm,800mm,900mm,1000mm,1200mm
	Ral9004; Ral9005; Ral7035

Doors

- Steel casement door
- Smoky-gray glass door
- Smoky-gray glass door with frame punched
- Perforated steel door
- Double Perforated steel door
- Double swing steel door

ORDERING INFORMATION

PART NUMBER	WIDTH	DEPTH	HEIGHT
APFS-6618	600	600	1000
APFS-6818	600	800	1000
APFS-6118	600	1000	1000
APFS-8818	800	800	1000
APFS-8118	800	1000	1000

